



BRINE TANK
BT DIAMETER

RESIN TANK
RT DIAMETER

RESIN TANK
RT DIAMETER

DRAIN
FLOW CONTROLLER

2" RAW WATER INLET
30-100 PSI

2" SOFTENED
WATER OUTLET

2" INLET
ISOLATION VALVE

2" BY-PASS VALVE
(NORMALLY CLOSED)

FLOW SENSOR

2" FLECK 2900
CONTROL VALVE

2" OUTLET
ISOLATION VALVE

BRINE TUBING

1" OUTLET TO DRAIN

NOTES:

ALL PIPING, FITTINGS, ETC SHOWN WITH DASHED LINES
ARE PROVIDED BY OTHERS.

GENERAL PLUMBING CONNECTIONS ARE SHOWN FOR
CLARITY ONLY.

DIMENSION TABLE		MGT-_____	
L= _____	RT= _____		
W= _____	BT= _____		
H= _____			

REVISIONS			
NO.	DATE	BY	REMARKS



MGT TWIN ALTERNATING WATER SOFTENER 2900 VALVE GENERAL ARRANGEMENT			
FRAC. ±	DEC. ±	FILE ID.	
DRN. ±	AJJG	SCALE	SHEET 1 OF 1
APPD.		DRAWING NO.	MGT TWIN ALT 2900
DATE	3/4/2009		REV.