



2.5" SERIES REVERSE OSMOSIS UNITS						
MODEL	DIMENSIONS L x W x H	PIPING CONN			MOTOR HP	MAX. GPD @ 77°F
		INLET	PERMEATE	REJECT		
MRO-200	22" x 7" x 31"	1/4" TUBE	1/4" TUBE	1/4" TUBE	N/A	200
MRO-300	28" x 7" x 33"	3/8" TUBE	3/8" TUBE	1/4" TUBE	N/A	300
MRO-500	20" x 14" x 27"	3/4" NPT	3/8" TUBE	3/8" TUBE	1/3	500
MRO-1000	20" x 14" x 27"	3/4" NPT	3/8" TUBE	3/8" TUBE	1/2	1000
MRO-1500	23" x 19" x 46"	3/4" NPT	3/8" TUBE	3/8" TUBE	3/4	1500
MRO-2500	23" x 19" x 46"	3/4" NPT	3/8" TUBE	3/8" TUBE	3/4	2500

RO STORAGE TANKS HIGH QUALITY POLYETHYLENE CONSTRUCTION WITH VENTED ACCESS OPENING	
CAPACITY	DIA. X HEIGHT
160 GAL.	28" x 66"
300 GAL.	35" x 81"
500 GAL.	46" x 76"
750 GAL.	46" x 119"
1000 GAL.	64" x 81"
1500 GAL.	64" x 121"
2000 GAL.	64" x 144"

REPRESSURE PUMP SPECIFICATIONS	
FLOW	20 GPM MAX.
PRESSURE	45 PSI MAX.
DIMENSIONS	23" L x 9" W x 13" H
HP	3/4
POWER	120V/60HZ/1PH
PIPING CONN.	1" NPT
WETTED CONSTRUCTION	304SS/ NORLYL

REVISIONS			
NO.	DATE	BY	REMARKS



MRO-2.5 SERIES RO SKID MOUNTED WITH PRETREATMENT STORAGE, AND PRPRESSURE			
TRAC #	DEC #	FILE ID.	SCALE
AGG			
DATE	2/24/2009	DRAWING NO.	5-242-4
SHEET 1 OF 1			REV. 1