



2.5" SERIES REVERSE OSMOSIS UNITS

MODEL	DIMENSIONS L x W x H	PIPING CONN			MOTOR HP	MAX. GPD @ 77 F
		INLET	PERMEATE	REJECT		
MRO-200	22" x 7" x 31"	1/4" TUBE	1/4" TUBE	1/4" TUBE	N/A	200
MRO-300	28" x 7" x 33"	3/8" TUBE	3/8" TUBE	1/4" TUBE	N/A	300
MRO-500	20" x 14" x 27"	3/4" NPT	3/8" TUBE	3/8" TUBE	1/3	500
MRO-1000	20" x 14" x 27"	3/4" NPT	3/8" TUBE	3/8" TUBE	1/2	1000
MRO-1500	23" x 19" x 46"	3/4" NPT	3/8" TUBE	3/8" TUBE	3/4	1500
MRO-2500	23" x 19" x 46"	3/4" NPT	3/8" TUBE	3/8" TUBE	3/4	2500

RO STORAGE TANKS
HIGH QUALITY POLYETHYLENE CONSTRUCTION WITH VENTED ACCESS OPENING

CAPACITY	DIA. X HEIGHT
160 GAL.	28" x 66"
300 GAL.	35" x 81"
500 GAL.	46" x 76"
750 GAL.	46" x 119"
1000 GAL.	64" x 81"
1500 GAL.	64" x 121"
2000 GAL.	64" x 144"

REPRESSURE PUMP SPECIFICATIONS

FLOW	20 GPM MAX.
PRESSURE	45 PSI MAX.
DIMENSIONS	23" L x 9" W x 13" H
HP	3/4
POWER	120V/60HZ/1PH
PIPING CONN.	1" NPT
WETTED CONSTRUCTION	304SS/ NORYL

- NOTE:**
1. STORAGE TANK AND REPRESSURE PUMP SYSTEM INCLUDES ALL FLOAT SWITCHES, VALVES, TUBING, AND GFI RECEPTACLES SHOWN.
 2. PRETREATMENT INTERCONNECTING PIPING, VALVES, ETC. SHOWN IN BROKEN LINES ARE BY OTHERS.

REVISIONS

NO.	DATE	BY	REMARKS



MRO-2.5 SERIES RO WITH PRETREATMENT STORAGE TANK AND MQ REPRESSURE PUMP

TRAC	DEC	FILE ID.	
AGG		SCALE	SHEET 1 OF 1
DATE		DRAWING NO.	5-242-3